



# 5 MM HIGH PRESSURE NMR CELL



High pressure NMR research has long been the domain of a few specialized labs around the world. Performing such experiments required extensive experience with high pressure hardware and carried with it an element of risk.

This has changed with the introduction of the first commercial NMR cell capable of repeated and safe use at 43,510 psi (3,000 bar). Daedalus Innovations' proprietary and patented zirconia NMR tube has an large internal diameter (2.8 mm / 3 mm) and a 5 mm outer diameter. This gives a surprisingly large active volume that makes the full range of triple-resonance experiments at high pressure readily accessible. The cell manifold easily assembles by threading the base piece to the main body component and tightening together to set the single-use seal. Modification of the NMR spectrometer or probe is not needed, and the cells are fully compatible with modern cryoprobe technology. High pressure tube assemblies compatible with either Bruker or Agilent probes are available.

The wetted parts are chemically compatible with most solvents making this cell useful for a wide array of applications in multiple research areas: biophysics, petroleum industry, chemical process monitoring, gas phase studies, materials science, geology, and deep-sea research.

Visit our website at [www.daedalusinnovations.com](http://www.daedalusinnovations.com) for other high pressure NMR products.



200 Racoosin Drive, Suite 106  
Aston, PA 19014  
United States

Phone: 610-358-4728  
Fax: 610-361-8509  
E-mail: [sales@daedalusinnovations.com](mailto:sales@daedalusinnovations.com)  
[www.daedalusinnovations.com](http://www.daedalusinnovations.com)

<b>Wetted parts</b>	Titanium (Bruker), zirconia (NMR tube), Viton
<b>Tube dimensions</b>	<b>Tube section:</b> 5 mm O.D. x 87 mm length 3,000 bar: 2.8 mm I.D. 2,500 bar: 3.0 mm I.D. <b>Head section:</b> 8 mm O.D. x 5 mm length
<b>Tube volume</b>	0.54 mL (3,000 bar) / 0.64 mL (2,500 bar)
<b>Temperature range</b>	5°C - 100°C using standard seals @ 2,500 bar -15°C - 125°C with specialized seals @ 2,500 bar
<b>Pressure range</b>	Stock versions available to 3,000 bar
<b>Pressure connection</b>	Manifold port is HiP HF2 (1/2"-20 UNF) for use with 1/8" tubing.
<b>Allowed fluids</b>	All fluids compatible with the wetted parts can be used in the cell. Examples are water, alcohols, alkanes, carbon dioxide, and xenon.